



Status Update @ New York IMAGES

Integrated Modeling for Analysis and Generation of

Rajkumar & Bruce Krogh Carnegie Mellon University

Approved for Public Release, Distribution Unlimited



Administrative



Project Title:	IMAGES: <u>Integrated Modeling for</u> <u>Analysis and Generation of Embedded</u> <u>Software</u>
PM:	Dr. John Bay
PI:	Profs. Raj Rajkumar and Bruce Krogh
Co-PIs:	Prof. Ed Clarke (CMU CS), Dr. Peter Feiler (CMU Software Engineering Institute) and Prof. John Lehoczky (CMU Statistics)
PI(s) Phone No. and e-mail:	(412) 268-8707 ; raj@ece.cmu.edu (412) 268-2472 ; krogh@ece.cmu.edu
Company/Instituti on:	Carnegie Mellon University
Contract Number:	F33615-00-C-1701
Award End Date:	June 22, 2003



Subcontractors and




Subcontractors and their roles	•None	
MoBIES Non-OEP Collaborators	 Lockheed Martin Aerospace, Upenn, Teknowledge and Vanderbilt 	
Non-OEP Collaboration Goals	• LM: Applicability of IMAGES tools	
	• Vanderbilt: Interchange format	
	• Penn: Model-checking coordination	
	• Teknowledge: UML Interface tool support	
SEC Collaboration Efforts	•None (so far but open)	



Problem Description and Project Objective (1)





Measurements

Environment

Multi-View Modeling + Analyses + Targeting Freedom + *Reusable* Embedded Software



Problem Description and Program Objective (2)



OEP	Avionics	Automotive
Technica l capabiliti es	 End-to-end Timing and Schedulability analysis Concurrency modeling ✓ Deployment control ✓ Event dependency modeling ✓ Composition of multiple dimensions Fault tolerance modeling 	 End-to-end Timing analysis RTOS environment modeling and optimization Off-line QoS trade-offs and optimization
Tool capabiliti es	 Inter-operability with UML and Timing Analysis tools ✓ Multiple views ✓ XML-based data interchange ✓ Configurator capabilities 	 Interoperability with Modeling and Analysis Tools OSEK-target code generation
Success	• Reusability of real-time	Timing predictability

OSEK target

ontimization

software

Criteria



Tool Descriptions



Time Weaver

- A framework and tool for creating reusable embedded software components for distributed real-time systems
- Capture, analyze and optimize nonfunctional aspects
 - Optimize inter-process communications and degree of concurrency
 - Customize timing parameters
 - Manipulate data path, control path and timing paths independently
- Generate fully functional target code by linking with functional code segments
- TimeWiz
 - End-to-end timing analysis tool for distributed RT systems




Embedded System





- Functional aspects (application functionality)
 - Computational activities that transform data from input to output
- Deployment aspects (system infrastructure)
 - Connect components
 - Distribute load
 - Specialized hardware

Reliability





Modality Support







Challenge:

- There are potentially hundreds or thousands of such "component modes"
- The system can move between different system modes
 - E.g. from "attack mode" to "fast escape" mode


Benefit:

- Model various modes explicitly
 - Correct code generation
- Perform worst-case timing analysis across the <u>entire</u> system
 - Current state of the art: use



Modality Primitives






Sub-system 1



Modality Composition





Sub-system 1

Sub-system 2



Modality View




- Explicitly model and control which components are enabled/disabled.
 - Conditional execution can also be represented
- Complete understanding and characterization of the "worst-case" behavior of the system.
 - Not just "representative"
 cases
- Code

 targe

 comp

 landstrange

 landstrang





Semantic Orthogonality



- Orthogonal semantics are operated in different views
- •Impact of changes (if any) in one dimension are automatically updated in other Modality

Pie Dod. Pythorone

Components

Components

Components

Components

Components

Secured Chycle

Sound Chycle

Soun


e.g. replication and processor binding Concurrency | Fault Tolerance




Deployment View



- Model component bindings to physical processors
 - Bindings will be done automatically based on timing analysis (later)
- Replication of components will place automatic constraints on









Event Flow View



- Primary modeling view to represent communications and interactions between components
- Multiple communication paradigms can be chosen
 - Publish/subscribe event flows
 - Unicast->multicast protocols

- Direct function invocation







Time Weaver • Compositionality hancements



- - Multiple orthogonal views
 - single view → 4 views
- Multiprocessor modeling
 - End-to-end timing analysis
- Event Modeling and System Modalities
 - Systems often operate in different modes
 - Component modes and system-wide modes
- Modeling
 - Scalability:
 - # of components
 - Fixed: workarounds to serious Java graphics inefficiency
 - File saving:
 - Any and all models can be saved even if not connected
 - Usability speed:
 - Graphics inefficiency fix also fixes usability speeds
- Meta-modeling
 - Need to present a visual interface








Characteristics (2)		
Current constraint	• Cannot <i>automatically</i> reverse-engineer systems	
Tool inputs	• Rational Rose UML Diagrams (class diagram and sequence diagrams)	
Tool outputs	 TimeWiz hardware & software configuration diagrams Generated RT-Java code that can run on RTOS targets 	
Meta-model	 Port-based objects for inter-component communications Components can be composed from components All inter-component communications happen through "Couplers" Components can have application agents (for functional behavior), state agent and protocol agent. 	
Tools interfaced	• Rational Rose, TimeWiz, Teknowledge UML Interface	



QoS Tradeoff &



QoS-based Resource Allocation Model (Q-RAM)



Resource

- The system consists of multiple applications
 - Each application is characterized by
 - Multiple QoS dimensions
 - Latency, encryption level, availability, ...
 - Data frame-rate, data resolution, window size, audio sampling rate, ...
 - Multiple resource requirements
 - CPU cycles, disk
- Maximize bandwidth network by bandwidth
 - Appropriately allocating finite - Utility curves express system resources to applications satisfaction along *each* QoS dimension



Q-RAM Results



- Replication requirements (e.g. for radar processing) create a multiple resource allocation problem
- The older Q-RAM algorithms for multiple resource allocation do not do well with fault-tolerance requirements
 - We have developed two new algorithms: amrmd_dp and amrmd_cm
 - amrmd_dp has higher run-time complexity
- amrmd_cm performs well
 - Admits the most number of tasks (by a significant margin)
 - Performs much better even if the number of processor choices is rather limited
 - Delivers the best utility of known algorithms
 - Has only slightly worse run-time behavior than amrmd1

Future Work



Time Weaver → OSEK



- Time Weaver generates Real-Time Java code and (Real-Time) CORBA interfaces for distributed system execution
 - Tool framework is generic, however
- Goal: Generate C/C+ + code for OSEK target
 - OSEK OS, COM and OIL collection studied in detail
- Separate local and non-local interaction interfaces
- Multiplicity of

- Minimum portability requirements & conformance classes
 - 8 basic/16 extended priorities: footprint vs. portability
 - 1 alarm: single periodic application task
- Tasks: Fixed priority preemptive scheduling
 - Multiple local dispatch/interaction mechanisms
 - Explicit activation, events: Task topology in application code
 - Non-uniform dispatch request queuing & task initialization
- Events: Binary task flag
 - Lossy communication & dispatch mechanism
 - Non-deterministic non-FIFO priority level task queuing
- Resources
 - Stateless task non-preemption via priority ceiling protocol
 - Unnecessary basic, internal, linked resource mechanisms
- Alarms



Time Weaver→OSEK OIL 2.3 System Modeling



- Task and communication architecture
 - Single processor only
 - Multiple task configurations: Incomplete application mode support
 - Portability limitation: Task topology embedded in application code
 - Not quite MetaH a DARPA EDCS/DASADA technology & emerging SAE AADL standard
- Scheduling analysis
 - Periodicity via alarm initialization: changeable by application code
 - Incomplete task dispatch information: explicit activation excluded
 - Missing timing properties
- Auto-generation of code
 - Runtime executive with application code as plug-in

COM2.2.2 and 3.0 Common features

- Local and network communication
- Queued and unqueued messages
- Direct and periodic transfer
- Topology in OI

Proliferation of mechanisms in support semanting me efficiency

COM 2.2.2

1:n communication
Send, xfer, receive
Single queue receiver
Send/Rec without
copy
Message initialization

gaps

COM3.0 m:n communication

Pack, send, xfer, receive
Multiple queue receivers
Zero length msg: event
alternative
Msg filter: zero length msgs
excluded




Avionics OEP Participation



Roles:

- End-to-end timing & schedulability analysis
- Concurrency modeling
- Inter-Process Communications modeling
- Java and CORBA code generation
- Tool interoperability
- Mid-Term Experiments
 - Timing and schedulability analysis
 - Concurrency & comm optimization
 - Configurator
 - Interfacing with UML diagra
 - Tool interoperability



Also worked with STRIVE project with Lockheed Martin

- Expected technology transition t o
 F-35
- Time Wiz → F-35



Automotive OEP



- Participation
 End-to-end Timing and Schedulability **Analyses**
 - Processor allocation
 - QoS modeling based on application utility functions (reward as a function of QoS)
- Automotive OEP
 - OSEK analysis and optimization
 - Technical Points of Contact:
 - Anouck Giraud at Berkeley
 - Bill Milam at Ford



Interactions with • Annotate Rose objects:

- - Represent object models in Rose adding tagged values to represent additional data.
- Rose←→TimeWeaver
 - Feed Time Weaver's analysis results back to Rose
- Incremental analysis
 - Tailor Time Weaver in such a way that it can do partial model checking based on changes in Rose only.
 - Longer term



Project Status Update



Technology Update

- Analyzable and reusable software component framework
- Multiple semantically orthogonal views
- QoS requirements can be specified and optimized with given resources
- Concurrency modeling and inter-process communication modeling
- Event dependency modeling and analysis capabilities
- Consistent XML interface to all tools of interest
- Can work with CORBA code

Tool Update

- Inter-operability between tools
 - Boeing OEP requirements: ACL, Configurator and model representation
- Time Weaver Release: http://www.cs.cmu.edu/~rtml
 - Completely new (better and friendlier) GUI for tool



Status Update (2)



OEP Participation

- Successful mappings to avionics context
 - Detailed feedback from Boeing, UCB and Lockheed Martin experiments
- OSEK studies in automotive context
 - Currently choosing from multiple options supported by OSEK



6-month Project Plans



Avionics OEP

- Apply feedback from Boeing and Lockheed Martin evaluations
 - Scalability and usability verification
 - Extensive documentation
- Scalability support: aggregation and encapsulation
- Fault-tolerance modeling, modality analysis and C/C++ support

Automotive OEP

- Model ETC dual-processor and cruise control environments
 - Analyze and optimize OSEK-based implementations
- Specific performance goals
 - Efficient support for automotive OEP and platforms
 - Instrumentation support
 - Lower processor and network utilization by automated optimization of # of threads, and communications.



Milestones and Schedule



- 1. Concurrency and Timing Analysis
 - 2QFY01: Timing and schedulability analysis
 - 3QFY02: End-to-end timing analysis
- 2. Constraint-Based Composition
 - 2QFY02: Event dependency modeling
 - 1QFY03: Replication modeling and replication support
- 3. Code Generation
 - 2QFY02: Real-Time Java code generation
 - 3QFY02: C++/Real-Time CORBA
 - 4QFY02: OSEK code generation
- 4. Model-Checking
 - 1QFY02: Transmission control property verification
 - 1QFY02: Worst-case execution time determination
- 5. QoS Tradeoff Support
 - 1Q02: QoS Specification and tradeoffs
 - 3Q02: Scalability
- 6. Tool Integration and Collaboration with OEPs
 - 2QFY02: Boeing and LM OEP mid-term experiments
 - 4QFY02-3QFY03: Avionics and Automotive OEP







- DoD contractors
 - Boeing
 - Lockheed Martin
 - Raytheon
- OMG Standardization
 - Real-time software component models
 - Interoperability with Real-Time UML
- TimeSys Corporation (www.timesys.com)
 - Commercial vendor of the TimeWiz timing analysis tool and TimeSys Linux with hard real-time and QoS support.
 - TimeWiz extensions from CMU to be returned to TimeSys for commercialization